

One vision, Two sharp eyes with Our Innovation

# RC-800

Simple and Speedy Measurement

## AUTO REFKERATOMETER



- Highly Accurate
- Simple to Use
- Diameter Measurement of Cornea and Pupil
- High Speed Printer
- Auto Shot
- Color Touch Screen

One vision, Two sharp eyes with Our Innovation

# RC-800

AUTO REFKERATOMETER



- Highly Accurate
- Simple to Use
- Diameter Measurement of Cornea and Pupil
- High Speed Printer
- Auto Shot
- Color Touch Screen

## Refractometry

Simple handling of the fine adjustment and measurement by yourself. Fogging is applied automatically for each measurement for more accurate results.

## Keratometry


Short consecutive measurements and time provide reliable data. Measurements at  $\phi 3.0\text{mm}$  (R = 8.0mm) give you enough information for contact lens fitting.

## Diameter Measurement of Cornea and Pupil

Easy measurement by moving the two cursors on the display to the boundaries of Cornea or Pupil.

## Language Selection

RC-800 has a Multi-language function. You can select your required language from "English", "Japanese", "German", "Chinese", "Spanish", "Spanish Latin America", "Italian", "Portuguese", "French" and "Russian".



## RC-800 SPECIFICATIONS

### Measurement Ranges

#### Refractometry

Sphere: -25.00D to +22.00D (VD=12.0mm)  
 Cylinder: 0D to  $\pm 10.00\text{D}$  (VD=12.0mm)  
 Axis: 0° to 180°  
 Minimum Pupil Dia:  $\phi 2.0\text{mm}$   
 Measurement time: 0.2 second/single eye (data taking time)

#### Keratometry

Range: 5.00mm to 11.00mm  
 Corneal Refraction: 30.68D to 67.50D (n=1.3375)  
 Corneal Astigmatism: 0D to 10D (n=1.3375)  
 AXIS: 0° to 180°  
 Measurement area:  $\phi 3\text{mm}$  (at 8.00mm corneal curvature)  
 Measurement time: 0.1 second/single eye (data taking time)

PD Measurement range 50 to 86mm

#### Corneal diameter measurement

Measurement range: 10.0 to 14.0mm  
 Display unit: 0.1mm

#### Pupil diameter measurement

Measurement range: 1.0 to 10.0 mm  
 Display unit: 0.1mm

#### Built-in Printer

Thermal printer

#### Data output type

RS232C / USB

#### Display

5.7 inch color liquid crystal display

#### Dimensions and weight

297(W)x500(D)x448(H)mm

#### Approx.

17kg

#### Power Requirements

AC 100V to 240V

50 / 60 Hz

80VA to 100VA



### Tomey Corporation [Asia-Pacific]

2-11-33 Noritakeshinmachi  
 Nishi-Ku, Nagoya, 451-0051, Japan  
 Tel: ++81-52-581-5327  
 Fax: ++81-52-561-4735  
 E-Mail: intl@tomey.co.jp

### Tomey GmbH [Europe]

Am Weichselgarten 19a  
 91058 Erlangen, Germany  
 Tel: ++49-9131-77710  
 Fax: ++49-9131-777120  
 E-Mail: info@tomey.de

For more information, visit our web site <http://www.tomey.com>

©2013 Tomey Corporation. Specifications are subject to change without notice. Any products mentioned herein are registered trademarks of their respective owners.